




JENTEC TECHNOLOGY CO., LTD

JTA0409 61W Switching Adapter Series

FEATURES	SPECIFICATIONS
	<p>Input Characteristics</p> <p>Voltage 90 ~ 264Vac Frequency 47 to 63Hz Inrush Current 30A Max. @ 115Vac Conducted EMI BSMI, CISPR22 class B Isolation <u>100M OHM at 500 VDC.</u> Leakage Current 3.5mA Max.</p> <p>Output Characteristics</p> <p>Hold-up Time 10mS . @ 115Vac Short Circuit Protection Continuous Over Voltage Protection Option</p> <p>Environmental Characteristics</p> <p>Operating Temperature 0 ~ 40°C Storage Temperature -25 ~ +85°C</p> <p>Mechanical Characteristics</p> <p>Dimensions 145 x 65 x 45 m/m Weight 532.2 g AC Inlet IEC 320-C14</p>



Model	Output Voltage	Output Current	Ripple & Noise	Line Regulation	Load Regulation
JTA0409A	5V	5.0 A	200mV	+/-1%	+/-5%
	12V	3.0 A	200mV	+/-1%	+/-5%

JENTEC TECHNOLOGY CO., LTD.

17F-10, No.2, Jian-Ba Rd .Chung-Ho City ,Taipei Hsien , Taiwan ,R.O.C

TEL: (886)2-8226-2057

FAX:(886)2-8226-2077